Jeep Cherokee Tail Light Housings

DISCLAIMER- THIS PRODUCT IS FOR OFFROAD USE ONLY ALL DIRECTIONS ARE THE SAME FOR BOTH DRIVER'S AND PASSENGER SIDE OF VEHICLE

Stock Tail Light Housings-

- Start by opening the rear hatch on your Jeep Cherokee XJ
- Locate the four screws securing the stock tail light housings in place
- Remove the 4 screws and set them out of the way so as to not misplace them

You Will Need:

- Ratchet
- Wrench
- Sockets
- Remove the lights from the rear of the stock tail light housings
- Remove the light bulbs from the plugs and mark them accordingly

You Will Need:

- Any type of marking device such as a permanent marker
- Trim all wires as close to the bulbs as possible while making sure to remember which wires go to the brake lights, turn signals, and reverse lights

You Will Need:

- Any type of wire cutters or pliers

Converter to Vehicle-

- Connect the green wire coming from the black converter box to the tan wire coming from your Jeep
- Connect the red wire coming from the black converter box to the to the white/brown wire coming from your Jeep
- Connect the brown wire coming from the black converter box to the blue/red wire coming from your Jeep

- Connect the white wire coming from the black converter box to any ground wire coming from your jeep

Reverse Light-

- Connect the brown/green wire coming from the reverse light directly to the black wire coming from your Jeep. Ensure this connection bypasses the converter
- Connect the white wire coming from the reverse light to any ground coming from your Jeep. Ensure this connection bypasses the converter

Installing the New Housings-

- Place the black rubber gromets into their respective locations on the new tail light housings
- Pushing from the opening in the rear of the new housings, insert the lights into their respective locations
- Set the new housings in place. Ensure the holes for the screws are all aligned properly
- Insert the four stock housing screws into the holes in such a way that they will secure the new housings to your Jeep Cherokee
- Ensure that all four screws are properly tightened

You Will Need:

- Ratchet
- Wrench
- Sockets

Links and Other Media: Affordable Offroad Website- https://affordableoffroad.com/ Jeep Cherokee XJ Main Pagehttps://affordableoffroad.com/product-category/jeep-cherokee-xj-84-01/