

Jeep Wrangler JK Inner Fenders

Removing the Stock Inner Fenders-

- 1) Locate the three 3/8" screws holding the stock plastic inner fenders in place
- 2) Remove the 3/8" screws and set them to the side. These will be used later in the installation

You Will Need:

- A ratchet, wrench, or impact
 - 3/8" wrench or socket
- 3) Remove the stock inner fender

Installing the New Inner Fenders-

- 1) Set the new inner fender in place and ensure that the existing holes in the new inner fender align with the holes from the stock inner fender
- 2) Insert the three stock 3/8" screws from steps 1&2 back into their respective places in such a way as to secure the new inner fender to the vehicle
- 3) Tighten the three screws to secure the new inner fenders to the vehicle
- 4) Locate the parts of the new inner fender that lay over the body mount and that lays over part of the body close to the front door
- 5) Using the provided speed screws, secure the new inner fender to the vehicle

You Will Need:

- An impact driver or drill
 - 3/8" socket
- 6) Repeat for installing the passenger side inner fender

Links and Other Media:

Affordable Offroad Main Page- <https://affordableoffroad.com/>

Affordable Offroad JK Page- <https://affordableoffroad.com/product-category/jeep-wrangler-jk-07-16/>

Reference Pictures:

