

## Jeep Grand Cherokee 50" Light Bar Brackets

**DISCLAIMER- ALL DIRECTIONS ARE THE SAME FOR BOTH DRIVER'S AND PASSENGER SIDE OF VEHICLE**

### **Driver's Side-**

- 1) Open driver's side front door and locate the rubber weather seal around the doorframe
- 2) Peel back the rubber weather seal until door frame is exposed
- 3) Place the driver's side 50" light bar bracket in the door frame
- 4) Measure 11" from the edge of the driver's side backdoor forward  
**You Will Need:**
  - Tape Measure
- 5) Once the driver's side 50" light bar bracket is 11" from the rear door, mark the three holes in the bottom of the bracket with a marker  
**You Will Need:**
  - Any type of marking device such as a marker or a scribe
- 6) After the holes are marked, remove the driver's side 50" light bar bracket from the work area
- 7) Drill the three holes in the door frame. Each hole at the marks you made earlier  
**You Will Need:**
  - Any type of handheld power drill
  - 3/16" twist drill bit
- 8) Once the three holes have been drilled through the driver's side door frame, place the driver's side 50" light bar bracket back in the door frame
- 9) Align the three holes that were drilled in the door frame with the three holes in the bottom of the light bar bracket
- 10) Using rivets, secure the bracket to the door frame  
**You Will Need:**
  - Any type of rivet gun
  - 3/16" rivets
- 11) Once the driver's side 50" light bar bracket is riveted to the door frame securely, reattach the rubber weather seal to the door frame

### **Links and Other Media:**

Affordable Offroad Website- <https://affordableoffroad.com/>

Reference Pictures-

Step 4



Steps 8/9



Steps 8/9/10



Step 11

